

All louvers shown meet some or all Florida and International Building Code Requirements for the hurricane-prone region.

Model Name Max. Wind-load	Construction Description Dimensions – inches (mm)	500-L AMCA Certifications	AMCA Listed	Miami-Dade County, FL NOA No.	Florida Product Approved No.	Florida Test Protocols	Minimum Opening	Maximum Section	Maximum Opening
							Dimensions – inches (mm)		
<b>Miami-Dade Approved Louvers</b>									
<a href="#">1606DHPM</a>	6" (152) deep, extruded aluminum stationary louver with high performance horizontal drainable blades	Water, Air	AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)	<a href="#">23-0724.23</a> <a href="#">EXP. 08-30-2028</a>	28078.3		12 W x 12 H (305 x 305)	72 W x 120 H (1829 x 3048)	Unlimited Width x 120 H (Unlimited Width x 3048 H)
150 PSF									
<a href="#">1606CM</a>	6" (152) deep, extruded aluminum combination horizontal blade louver / airfoil blade damper		AMCA 540 Basic Level D AMCA 550 (with blades closed)	<a href="#">23-0823.04</a> <a href="#">EXP. 11-2-2028</a>	41947.2		12 W x 16 H (305 x 406)	60 W x 120 H (1524 x 3048)	
120 PSF									
<a href="#">1605WDM</a>	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant horizontal blades		AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)	<a href="#">23-0724.24</a> <a href="#">EXP. 08-30-2028</a>	28078.1		12 W x 12 H (305 x 305)	72 W x 120 H (1829 x 3048)	
150 PSF									
<a href="#">1609HM</a>	9" (229) deep, extruded aluminum stationary hybrid with wind-driven rain resistant louver horizontal front and rear vertical blades	Water, Air, & Wind Driven Rain		<a href="#">23-0823.05</a> <a href="#">EXP. 04-04-2029</a>	41947.1		12 W x 12 H (305 x 305)	60 W x 120 H (1524 x 3048)	
160 PSF									
<a href="#">1605WDVM</a>	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant vertical blades		AMCA 540 Enhanced Level E AMCA 550	<a href="#">23-0724.25</a> <a href="#">EXP. 08-30-2028</a>	28078.2		12 W x 12 H (305 x 305)	72 W x 120 H or 120 W x 72 H (1829 x 3048 or 1829 x 3048)	
130 PSF									
<a href="#">1675WDVM</a>	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant vertical blades			<a href="#">23-0724.22</a> <a href="#">EXP. 08-30-2028</a>	28078.4		12 W x 12 H (305 x 305)	48 W x 120 H or 120 W x 48 H (1219 x 3048 or 3049 x 1219)	
150 PSF									

Model Name Max. Wind-load	Construction Description Dimensions – inches (mm)	500-L AMCA Certifications	AMCA Listed	Miami-Dade County, FL NOA No.	Florida Product Approved No.	Florida Test Protocols	Minimum Opening	Maximum Section	Maximum Opening
							Dimensions – inches (mm)		
<b>Florida Product Approved Louvers</b>									
<a href="#">1604DHPF*</a>	4" (102) deep, extruded aluminum stationary louver with high performance drainable blade	Water, Air	AMCA 540 Basic Level D					48 W x 120 H or 120 W x 48 H (1219 x 3048 or 3049 x 1219)	40 sq. ft. (3.7 m2). Larger louvers require field assembly of smaller sections.
Up to 55 PSF †									
<a href="#">1606DHPF*</a>	6" (152) deep, extruded aluminum with horizontal drainable blade louver		AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)					108 W x 84 H or 84 W x 120 H (2743 x 2134 or 2134 x 2743)	Unlimited Width x 120 H (Unlimited Width x 3048 H)
Up to 150 PSF †									
<a href="#">1605WDF*</a>	5" (127) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade	Water, Air & Wind Driven Rain	AMCA 540 Enhanced Level E AMCA 550				12 W x 12 H (305 x 305)	72 W x 120 H or 120 W x 72 H (1829 x 3048 or 1829 x 3048)	
Up to 150 PSF †									
<a href="#">1606WDF*</a>	6" (152) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade								
Up to 150 PSF †									
<a href="#">1605WDVF*</a>	5" (127) deep extruded aluminum stationary louver with high velocity wind-driven rain resistant vertical blade								
Up to 130 PSF †									
<b>AMCA 540 &amp; AMCA 550 Listed Louvers</b>									
<a href="#">1606C</a>	6" (152) Deep, extruded aluminum combination louver/damper with high velocity wind-driven rain and impact resistant vertical blade	Water, Air	AMCA 540 Basic Level D AMCA 550 (with blades closed)				12 W x 16 H (305 x 406)	60 W x 120 H (1524 x 3048)	Unlimited Width x 120 H (Unlimited Width x 3048 H)
<a href="#">1609H</a>	9" (229) deep, extruded aluminum stationary hybrid louver with high velocity wind-driven rain and impact resistant horizontal and vertical blade	Water, Air & Wind Driven Rain	AMCA 540 Enhanced Level E AMCA 550				12 W x 12 H (305 x 305)	72 W x 120 H or 120 W x 72 H (1829 x 3048 or 1829 x 3048)	
<a href="#">1605WDV</a>	5" (127) deep, extruded aluminum stationary louver with high velocity wind-driven rain and impact resistant vertical blade								

\* Also available in architectural shapes. Contact factory.

† Size and Section dependent