



**SPECIALTY STATIONARY LOUVERS
EXTRUDED ALUMINUM
CIRCULAR & SEMICIRCULAR SHAPES
MODEL SERIES: 1600**

Nailor specialty shape louvers are available in a variety of blade/frame designs. The following louver models are available in specialty shapes as shown:

1602J	1604J	1604D	1606J	1606D
1602K	1604JD	1604DD	1606JD	1606DD
1602D	1604KD	1604Y	1606KD	1606DHP

Note: Use of drainable blades is not recommended on certain shapes. Consult Nailor for specific applications.

PERFORMANCE:

Standard louvers are tested for water penetration and pressure drop in a square configuration only. Performance of specialty shape louvers may vary from that of standard louvers.

Specialty shape louvers are not licensed to bear the AMCA seal.

STANDARD CONSTRUCTION:

FRAME: Type 6063-T6 extruded or formed aluminum. Channel type standard. Frame profile may vary depending upon louver style and shape. Contact Nailor for specific details.

BLADES: Type 6063-T6 extruded aluminum. See applicable louver model submittal sheet for blade profile.

BLADE SUPPORT BRACKETS: Concealed type, factory installed on rear of louver as necessary. Reinforced with 1 1/2" x 2" (38 x 51) vertical angle (adds approximately 2" [51] to overall louver depth).

SCREEN: 3/4" x .051 (19 x 1.3) expanded, flattened aluminum bird screen in removable frame, inside (rear) mount (adds approximately 3/8" [10] to louver depth).

FINISH: Mill.

MINIMUM SIZE: 20" (508) Diameter. Contact Nailor for smaller sizes.

MAXIMUM SINGLE SECTION SIZE: 120" W x 84" H (3048 x 2134) or 84" H x 120" W (2134 x 3048). Larger louvers will require field assembly of smaller sections. Consult Nailor for section details of specific sizes.

OPTIONS:

- FL** Flanged Frame.
- BSSS** Type 304 S.S. Bird Screen.
- BSN** No Bird Screen.
- ISA** Aluminum Insect Screen.
- ISSS** Type 304 S.S. Insect Screen.
- PAC** Perimeter Anchor Clips.
- Other:** _____.

OPTIONAL FINISHES:

- PC3** Powder Coat AAMA 2603. Color: _____.
- PC4** High Performance Powder Coat AAMA 2604 (Equivalent to 50% Kynar®). Color: _____.
- PC5** Fluoropolymer Powder Coat AAMA 2605 (Equivalent to 70% Kynar®). Color: _____.
- PCC** Prime Coat.
- AN04** Clear Anodized 204-R1.
- AN15** Clear Anodized 215-R1.

Color Anodized:

- ANLB** Light Bronze.
- ANDB** Dark Bronze.
- ANMB** Medium Bronze.
- ANBK** Black.


OPTIONAL W x H SIZING (1/4" [6.5] Undersize standard):

- U00** Exact Size.
- U38** Undersize 3/8" (9.5).
- U50** Undersize 1/2" (12.7).


Contact Nailor for special configurations or requirements.




CA Circle (Round)




CB Semi-Circle




CC 1/4 Circle Left




CD 1/4 Circle Right




CE Arch Semi-Circular




CFC Arch Custom (Dropped or Lancet)




CFE Arch Equilateral




CG Oval




CH Arch 1/4 Circle Left



CJ Arch 1/4 Circle Right



TYPICAL CHANNEL FRAME (STANDARD)



OPTIONAL FLANGED FRAME (FL)

Dimensions are in inches (mm)

SCHEDULE TYPE:

PROJECT:

ENGINEER:

CONTRACTOR:

DATE

B SERIES

SUPERSEDES

DRAWING NO.

2 - 17 - 22

1600

8 - 20 - 13R

1600CSC