

## PERFORMANCE DATA:

### Models 4302, 4302-DF, 4302-F, 4302A • Return Panel

Ceiling Module	Neck Velocity, FPM	200	300	400	500	600	700	800	900	1000
	Negative Static Pressure	.013	.029	.051	.080	.115	.157	.205	.259	.320
	Velocity Pressure	.002	.006	.010	.016	.023	.031	.040	.050	.063
12 x 12	Airflow, CFM	200	300	400	500	600	700	800	900	1000
	Noise Criteria	—	—	27	34	40	45	49	52	57
20 x 20	Airflow, CFM	556	833	1111	1389	1667	1944	2222	2500	2778
	Noise Criteria	—	—	24	30	37	42	46	49	54
24 x 12	Airflow, CFM	400	600	800	1000	1200	1400	1600	1800	2000
	Noise Criteria	—	17	27	32	39	44	48	52	56
24 x 24	Airflow, CFM	800	1200	1600	2000	2400	2800	3200	3600	4000
	Noise Criteria	—	16	24	31	37	41	45	48	53
48 x 24	Airflow, CFM	1600	2400	3200	4000	4800	5600	6400	7200	8000
	Noise Criteria	—	18	27	33	39	44	48	51	56

#### Performance Notes:

1. All pressures are in inches w.g..
2. Noise Criteria (NC) values are based upon 10 dB room absorption, re 10<sup>-12</sup> watts. Dash (—) in space indicates an Noise Criteria of less than 15.
3. Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70 – 2006.