

PERFORMANCE DATA:

Models 4330CB, 4330CBA, 4330CBAA • 12 x 12 (300 x 300) Module Size

Nominal Neck Size	Neck Velocity, FPM	300	400	500	600	700	800	900	
	Velocity Pressure	.006	.010	.016	.023	.031	.040	.051	
	Total Pressure	.030	.052	.082	.118	.162	.211	.267	
6" Dia.	Flow Rate, CFM	60	80	95	115	135	155	175	
	Throw	4-Way	1-2-4	2-3-6	2-4-7	3-5-7	3-5-8	4-6-9	5-6-9
		3-Way	2-3-6	2-4-8	3-5-11	4-6-12	5-7-13	5-8-14	6-10-15
		2-Way	2-4-8	3-5-11	4-6-13	5-8-15	6-9-16	7-11-18	8-12-20
		1-Way	3-4-9	4-6-12	5-8-16	6-9-18	7-11-20	8-12-22	9-14-23
Noise Criteria	16	22	27	32	37	41	44		
8" Dia.	Flow Rate, CFM	105	140	175	210	245	280	315	
	Throw	4-Way	2-3-6	2-4-8	3-5-9	4-6-10	4-7-11	4-8-12	5-9-12
		3-Way	2-3-7	3-4-9	3-5-11	4-7-12	5-8-13	6-9-14	7-10-14
		2-Way	3-4-9	4-6-13	5-8-15	6-9-17	7-11-18	8-13-20	9-14-21
		1-Way	3-5-11	5-7-15	6-9-18	7-11-21	8-13-22	10-15-24	11-17-25
Noise Criteria	17	23	29	35	39	43	46		
6 x 6	Flow Rate, CFM	75	100	125	150	175	200	225	
	Throw	4-Way	1-2-5	2-3-7	3-4-8	3-5-8	4-6-9	5-7-10	5-7-11
		3-Way	2-3-6	2-4-8	3-5-11	4-6-12	5-7-13	5-8-14	6-10-15
		2-Way	3-4-9	4-6-12	5-7-15	6-9-17	7-10-20	8-12-21	9-14-22
		1-Way	3-5-10	4-7-14	6-9-18	7-10-21	8-12-23	9-14-24	10-16-26
Noise Criteria	16	22	27	32	36	40	43		
8 x 8	Flow Rate, CFM	135	175	220	265	310	355	400	
	Throw	4-Way	2-3-6	3-4-9	3-5-10	4-6-11	5-8-12	6-9-13	6-10-14
		3-Way	2-3-7	3-5-10	4-6-12	5-7-13	6-9-14	7-10-15	7-11-16
		2-Way	3-5-11	4-7-14	6-9-17	7-11-20	8-13-21	9-14-23	11-16-24
		1-Way	4-6-12	5-8-17	7-10-21	8-12-23	9-14-25	11-17-27	12-20-28
Noise Criteria	17	23	30	36	40	44	47		

Models 4330CB, 4330CBA, 4330CBAA • 24 x 12 (600 x 300) Module Size

Nominal Neck Size	Neck Velocity, FPM	300	400	500	600	700	800	900	
	Velocity Pressure	.006	.010	.016	.023	.031	.040	.051	
	Total Pressure	.030	.052	.082	.118	.162	.211	.267	
6" Dia.	Flow Rate, CFM	60	80	95	115	135	155	175	
	Throw	4-Way	1-2-4	2-3-6	2-4-7	3-5-7	3-5-8	4-6-9	5-6-9
		3-Way	2-3-6	2-4-8	3-5-11	4-6-12	5-7-13	5-8-14	6-10-15
		2-Way	2-4-8	3-5-11	4-6-13	5-8-15	6-9-16	7-11-18	8-12-20
		1-Way	3-4-9	4-6-12	5-8-16	6-9-18	7-11-20	8-12-22	9-14-23
Noise Criteria	16	22	27	32	37	41	44		
8" Dia.	Flow Rate, CFM	105	140	175	210	245	280	315	
	Throw	4-Way	2-3-6	2-4-8	3-5-9	4-6-10	4-7-11	4-8-12	5-9-12
		3-Way	2-3-7	3-4-9	3-5-11	4-7-12	5-8-13	6-9-14	7-10-14
		2-Way	3-4-9	4-6-13	5-8-15	6-9-17	7-11-18	8-13-20	9-14-21
		1-Way	3-5-11	5-7-15	6-9-18	7-11-21	8-13-22	10-15-24	11-17-25
Noise Criteria	17	23	29	35	39	43	46		
6 x 6	Flow Rate, CFM	75	100	125	150	175	200	225	
	Throw	4-Way	1-2-5	2-3-7	3-4-8	3-5-8	4-6-9	5-7-10	5-7-11
		3-Way	2-3-6	2-4-8	3-5-11	4-6-12	5-7-13	5-8-14	6-10-15
		2-Way	3-4-9	4-6-12	5-7-15	6-9-17	7-10-20	8-12-21	9-14-22
		1-Way	3-5-10	4-7-14	6-9-18	7-10-21	8-12-23	9-14-24	10-16-26
Noise Criteria	16	22	27	32	36	40	43		
8 x 8	Flow Rate, CFM	135	175	220	265	310	355	400	
	Throw	4-Way	2-3-6	3-4-9	3-5-10	4-6-11	5-8-12	6-9-13	6-10-14
		3-Way	2-3-7	3-5-10	4-6-12	5-7-13	6-9-14	7-10-15	7-11-16
		2-Way	3-5-11	4-7-14	6-9-17	7-11-20	8-13-21	9-14-23	11-16-24
		1-Way	4-6-12	5-8-17	7-10-21	8-12-23	9-14-25	11-17-27	12-20-28
Noise Criteria	17	23	30	36	40	44	47		

For performance notes, see page D216.

PERFORMANCE DATA:

Models 4330CB, 4330CBA, 4330CBAA • 24 x 24 (600 x 600) Module Size • Round Neck

Nominal Neck Size	Neck Velocity, FPM		300	400	500	600	700	800	900
	Velocity Pressure		.006	.010	.016	.023	.031	.040	.051
	Total Pressure		.030	.052	.082	.118	.162	.211	.267
6" Dia.	Flow Rate, CFM		60	80	95	115	135	155	175
	Throw	4-Way	1-2-4	2-3-6	2-3-7	3-4-7	3-5-8	4-6-9	4-6-9
		3-Way	1-2-5	2-3-7	2-4-8	3-5-9	4-6-9	4-7-10	5-7-11
		2-Way	2-3-7	3-4-9	4-6-11	4-7-12	5-8-13	6-9-14	7-11-15
		1-Way	2-4-8	3-5-11	4-7-13	5-8-15	6-9-16	7-11-17	8-12-18
Noise Criteria		—	19	25	30	34	38	41	
8" Dia.	Flow Rate, CFM		105	140	175	210	245	280	315
	Throw	4-Way	2-3-6	2-4-8	3-5-9	4-6-10	4-7-11	4-8-12	5-9-12
		3-Way	2-3-7	3-4-9	3-5-11	4-7-12	5-8-13	6-9-14	7-10-14
		2-Way	3-4-9	4-6-13	5-8-15	6-9-17	7-11-18	8-13-20	9-14-21
		1-Way	3-5-11	5-7-15	6-9-18	7-11-21	8-13-22	10-15-24	11-17-25
Noise Criteria		14	22	28	33	37	41	44	
10" Dia.	Flow Rate, CFM		165	215	270	325	380	435	490
	Throw	4-Way	2-3-7	3-5-10	4-6-12	5-7-13	5-8-14	6-10-15	7-11-16
		3-Way	2-4-8	3-5-11	4-7-13	5-8-15	6-10-16	7-11-17	8-13-18
		2-Way	4-6-12	5-8-16	6-10-20	8-12-22	9-14-23	10-16-25	12-18-27
		1-Way	4-7-14	6-9-18	7-11-23	9-14-26	11-16-28	12-18-29	14-22-31
Noise Criteria		16	24	30	35	39	43	46	
12" Dia.	Flow Rate, CFM		235	315	390	470	550	625	705
	Throw	4-Way	3-4-9	4-6-12	5-7-14	6-9-15	7-10-17	8-12-18	9-13-20
		3-Way	3-5-10	4-7-14	5-8-16	7-10-18	8-12-20	9-14-22	10-15-23
		2-Way	4-7-14	6-9-20	8-12-24	9-14-26	11-17-28	13-20-30	14-23-32
		1-Way	5-8-17	7-11-23	9-14-28	11-17-31	13-20-33	15-23-35	17-26-37
Noise Criteria		18	26	32	37	41	45	48	
14" Dia.	Flow Rate, CFM		320	425	535	640	750	855	960
	Throw	4-Way	3-5-10	4-7-14	5-8-16	7-10-18	8-12-21	9-14-22	10-16-23
		3-Way	4-6-12	5-8-16	6-10-20	8-12-22	9-14-24	10-16-25	12-18-27
		2-Way	5-8-17	7-11-24	9-14-28	11-17-30	13-21-33	15-24-35	17-26-37
		1-Way	6-9-20	8-13-27	11-16-33	13-20-36	15-24-38	17-27-41	20-30-43
Noise Criteria		21	29	35	39	44	48	51	
15" Dia.	Flow Rate, CFM		370	490	615	740	860	985	1100
	Throw	4-Way	3-6-10	4-2-14	5-8-17	8-10-19	8-13-21	10-14-23	10-16-24
		3-Way	4-6-12	6-8-17	6-11-21	8-13-22	10-14-25	11-16-26	13-18-28
		2-Way	4-8-17	7-12-25	9-15-30	11-18-31	13-22-34	16-25-35	17-27-38
		1-Way	6-9-20	8-14-28	12-17-34	14-21-37	16-24-39	18-27-42	17-31-43
Noise Criteria		22	30	36	40	45	49	52	
16" Dia.	Flow Rate, CFM		420	560	700	835	975	1115	1255
	Throw	4-Way	4-6-12	5-8-16	6-10-20	8-12-22	9-14-23	10-16-25	12-18-26
		3-Way	4-7-14	6-9-18	7-11-23	9-14-25	10-16-27	12-18-29	14-22-30
		2-Way	6-9-20	8-13-27	10-16-32	13-20-35	15-24-37	17-27-40	20-30-42
		1-Way	7-11-23	10-15-31	12-18-37	15-23-41	17-27-44	21-31-47	23-35-50
Noise Criteria		23	31	37	41	46	50	53	
18" Dia.	Flow Rate, CFM		530	705	885	1060	1235	1415	1590
	Throw	4-Way	4-7-14	5-9-18	7-10-20	9-13-24	10-16-26	10-19-28	13-21-29
		3-Way	4-7-17	6-10-21	8-12-24	10-15-28	11-20-30	13-22-32	17-24-34
		2-Way	7-10-23	10-14-29	11-17-34	15-22-36	18-28-43	20-30-44	24-34-50
		1-Way	8-12-26	11-17-33	14-21-40	18-25-45	21-32-50	23-38-53	29-40-56
Noise Criteria		25	33	39	43	48	52	55	

D
CEILING DIFFUSERS

For performance notes, see page D216.

PERFORMANCE DATA:

Models 4330CB, 4330CBA, 4330CBAA • 24 x 24 (600 x 600) Module Size • Square Neck

Nominal Neck Size	Neck Velocity, FPM	300	400	500	600	700	800	900	
	Velocity Pressure	.006	.010	.016	.023	.031	.040	.051	
	Total Pressure	.028	.050	.079	.113	.155	.202	.256	
6 x 6	Flow Rate, CFM	75	100	125	150	175	200	225	
	Throw	4-Way	1-2-5	2-3-7	3-4-8	3-5-8	4-6-9	5-7-10	5-7-11
		3-Way	2-3-6	2-4-8	3-5-11	4-6-12	5-7-13	5-8-14	6-10-15
		2-Way	3-4-9	4-6-12	5-7-15	6-9-17	7-10-20	8-12-21	9-14-22
		1-Way	3-5-10	4-7-14	6-9-18	7-10-21	8-12-23	9-14-24	10-16-26
Noise Criteria	—	20	26	31	35	39	42		
8 x 8	Flow Rate, CFM	135	175	220	265	310	355	400	
	Throw	4-Way	2-3-6	3-4-9	3-5-10	4-6-11	5-8-12	6-9-13	6-10-14
		3-Way	2-3-7	3-5-10	4-6-12	5-7-13	6-9-14	7-10-15	7-11-16
		2-Way	3-5-11	4-7-14	6-9-17	7-11-20	8-13-21	9-14-23	11-16-24
		1-Way	4-6-12	5-8-17	7-10-21	8-12-23	9-14-25	11-17-27	12-20-28
Noise Criteria	15	23	29	34	38	42	45		
10 x 10	Flow Rate, CFM	210	275	345	415	485	555	625	
	Throw	4-Way	2-4-8	3-5-11	4-7-13	5-8-14	6-10-16	7-11-17	8-12-18
		3-Way	3-4-9	4-6-13	5-8-15	6-9-17	7-11-18	8-13-20	9-14-22
		2-Way	4-6-13	6-9-18	7-11-22	9-13-25	10-16-26	12-18-28	13-21-30
		1-Way	5-8-16	7-10-22	8-13-26	10-16-29	12-18-31	14-22-33	16-25-35
Noise Criteria	17	25	31	36	40	44	47		
12 x 12	Flow Rate, CFM	300	400	500	600	700	800	900	
	Throw	4-Way	3-5-10	4-6-13	5-8-16	6-10-17	8-12-20	9-13-21	10-15-22
		3-Way	3-5-11	5-7-15	6-9-18	7-11-21	9-13-23	10-15-24	11-17-26
		2-Way	5-8-16	7-11-23	9-13-27	11-16-29	13-20-32	14-23-34	16-25-36
		1-Way	6-9-20	8-12-26	10-16-31	12-20-34	14-23-37	17-26-40	22-31-44
Noise Criteria	19	25	33	38	42	46	49		
14 x 14	Flow Rate, CFM	410	545	680	815	955	1090	1360	
	Throw	4-Way	1-1-6	1-3-8	2-4-11	3-6-13	4-7-15	5-8-17	7-11-22
		3-Way	1-3-10	2-6-14	4-9-18	6-10-21	8-12-26	9-14-29	11-18-32
		2-Way	2-5-14	4-9-19	7-12-24	9-14-30	11-17-35	13-19-40	16-24-47
		1-Way	3-8-17	6-11-23	9-14-30	11-17-36	13-20-42	15-23-48	19-30-54
Noise Criteria	22	30	36	40	45	49	52		
15 x 15	Flow Rate, CFM	470	625	780	935	1095	1250	1405	
	Throw	4-Way	4-6-12	5-8-17	7-10-21	8-12-23	10-15-25	11-17-26	12-20-28
		3-Way	4-7-14	6-9-20	8-12-24	9-14-26	11-17-28	13-20-30	14-23-32
		2-Way	6-10-21	9-13-28	11-17-33	13-21-37	16-25-40	18-28-42	21-32-45
		1-Way	8-12-25	10-16-33	13-21-39	16-25-43	18-29-46	22-33-49	25-37-53
Noise Criteria	23	31	37	41	46	50	53		
16 x 16	Flow Rate, CFM	530	710	890	1065	1245	1420	1600	
	Throw	4-Way	4-7-14	5-9-18	7-10-20	9-13-24	10-16-26	10-19-28	13-21-29
		3-Way	4-7-17	6-10-21	8-12-24	10-15-28	11-20-30	13-22-32	17-24-34
		2-Way	7-10-23	10-14-29	11-17-34	15-22-36	18-28-43	20-30-44	24-34-50
		1-Way	8-12-26	11-17-33	14-21-40	18-25-45	21-32-50	23-38-53	29-40-56
Noise Criteria	24	32	38	42	47	51	54		
18 x 18	Flow Rate, CFM	675	900	1125	1350	1575	1800	2025	
	Throw	4-Way	5-7-15	6-10-21	8-12-25	10-15-27	12-18-30	13-21-32	15-24-33
		3-Way	5-8-17	7-11-24	9-14-29	11-17-32	13-22-34	15-24-36	17-27-39
		2-Way	8-12-26	11-16-34	13-21-40	16-26-44	20-30-47	23-34-50	26-38-54
		1-Way	9-14-29	12-20-39	16-25-47	20-29-52	23-34-56	26-39-60	29-44-64
Noise Criteria	26	34	40	44	49	53	56		

Performance Notes:

- All pressures are in inches w.g..
- Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions.
- Noise Criteria (NC) values are based upon 10 dB room absorption, re 10⁻¹² watts. Dash (—) in space indicates an Noise Criteria of less than 20.

- Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70 – 2006.

Balancing:

It is recommended that a commercially available 'Flow Hood' is used for field balancing. The airflow meter directly reads average flow rate with great accuracy at all volumes. It is a much faster and more accurate alternative to time consuming multiple velocity readings, eliminating the use of Ak factors and the calculations required to convert the average velocity into airflow.