

## PERFORMANCE DATA:

### Models RNS and ARNS • 12 x 12 (300 x 300) Face Size

Nominal Neck Size	Neck Velocity, FPM	400	500	600	700	800	900	1000	1200	1400	1600
	Velocity Pressure	.010	.016	.023	.031	.040	.051	.063	.090	.122	.160
4" Dia.	Total Pressure	.014	.022	.032	.043	.056	.071	.088	.126	.172	.224
	Airflow, CFM	35	44	52	61	70	79	87	105	122	140
	Throw	1-2-4	2-2-5	2-3-5	2-3-6	2-4-7	3-4-7	3-5-7	4-5-8	4-6-9	5-7-9
	Noise Criteria	—	—	—	—	—	11	19	25	30	35
5" Dia.	Total Pressure	.017	.026	.038	.051	.067	.085	.105	.151	.206	.269
	Airflow, CFM	55	68	82	95	109	123	136	164	191	218
	Throw	2-2-5	2-3-6	2-4-6	2-4-7	2-5-8	3-6-9	4-6-9	5-7-10	5-8-11	6-8-11
	Noise Criteria	—	—	—	—	—	14	22	28	33	38
6" Dia.	Total Pressure	.018	.029	.043	.060	.079	.100	.128	.175	.250	.325
	Airflow, CFM	80	100	120	140	160	180	200	235	275	315
	Throw	1-2-4	1-2-5	1-3-6	2-3-6	2-4-8	3-4-8	3-4-10	4-5-10	4-6-14	5-8-14
	Noise Criteria	—	—	11	16	20	22	24	31	38	41
7" Dia.	Total Pressure	.022	.035	.050	.068	.089	.112	.138	.199	.271	.354
	Airflow, CFM	107	134	160	187	214	241	267	321	374	428
	Throw	2-4-8	3-5-9	4-6-10	4-7-11	5-8-12	5-9-13	6-10-14	7-10-14	9-11-15	10-12-16
	Noise Criteria	—	—	12	17	20	24	27	33	39	42
8" Dia.	Total Pressure	.031	.047	.065	.087	.110	.140	.168	.235	.310	.395
	Airflow, CFM	140	175	210	245	280	315	350	420	490	560
	Throw	3-5-9	4-5-11	5-7-13	5-8-14	6-9-14	6-10-15	7-11-16	8-12-17	10-13-18	11-14-18
	Noise Criteria	—	—	13	18	22	26	29	35	40	44

### Models RNS and ARNS • 20 x 20 (500 x 500) Face Size

Nominal Neck Size	Neck Velocity, FPM	400	500	600	700	800	900	1000	1200	1400	1600
	Velocity Pressure	.010	.016	.023	.031	.040	.051	.063	.090	.122	.160
6" Dia.	Total Pressure	.015	.023	.033	.045	.058	.074	.091	.130	.176	.230
	Airflow, CFM	80	100	120	140	160	180	200	235	275	315
	Throw	1-1-3	1-2-4	1-2-4	1-3-5	2-3-6	2-3-6	2-4-7	3-5-8	3-5-8	4-6-9
	Noise Criteria	—	—	14	18	21	26	29	34	38	41
8" Dia.	Total Pressure	.018	.028	.041	.055	.072	.091	.112	.161	.219	.286
	Airflow, CFM	140	175	210	245	280	315	350	420	490	560
	Throw	1-2-5	2-3-6	2-4-6	3-4-7	3-5-7	4-5-8	4-6-8	5-6-9	6-7-10	6-8-11
	Noise Criteria	—	11	16	20	23	28	31	36	40	43
10" Dia.	Total Pressure	.023	.036	.052	.071	.092	.117	.144	.207	.281	.367
	Airflow, CFM	220	270	330	380	435	490	545	655	765	870
	Throw	2-4-6	3-4-7	4-5-8	4-6-9	5-6-9	5-7-10	6-7-10	6-8-11	7-9-12	8-9-13
	Noise Criteria	—	13	18	22	25	30	33	38	42	45

#### Performance Notes:

- Throws are given at 150, 100 and 50 fpm terminal velocities, under isothermal conditions.
- All pressures are in inches w.g..
- The addition of quadrant blanks reduces the effective area and for a given air volume, increases the discharge velocity. This will result in an increase in throw, pressure drop and sound level. To determine throw, select the diffuser as if it were supplying a larger volume of air. The table shows the percentage increase required to determine selection of diffuser size and throw. To correct pressure drop and Noise Criteria, use correction factors as shown for 4-way blow values.

- Noise Criteria (NC) are based on a room absorption of 10 dB, re 10<sup>-12</sup> watts. Dash (—) in space denotes an Noise Criteria level less than 10.
- Data derived from independent tests conducted in accordance with ANSI/ASHRAE Standard 70-2006.

Neck Size Diameter in Inches	Nominal Overall Face Size	Ak Factor
6	12 x 12	.131
8	12 x 12	.202
6	24 x 24	.180
8	24 x 24	.227
10	24 x 24	.331
12	24 x 24	.450
14	24 x 24	.511
15	24 x 24	.625

Quadrant Blanks (Blow)	% Increase in Air Volume for Throw Determination	% Increase in Static Pressure Drop	NC Sound Level Increase
1 (3-way)	35	125	8
2 (2-way)	100	450	19

## PERFORMANCE DATA:

### Models RNS and ARNS • 24 x 24 (600 x 600) Face Size

Nominal Neck Size	Neck Velocity, FPM	400	500	600	700	800	900	1000	1200	1400	1600
	Velocity Pressure	.010	.016	.023	.031	.040	.051	.063	.090	.122	.160
6" Dia.	Total Pressure	.015	.023	.035	.045	.060	.076	.095	.135	.186	.240
	Airflow, CFM	80	100	120	140	160	180	200	235	275	315
	Throw	1-1-4	1-2-5	1-2-6	1-3-7	2-4-9	2-5-9	3-6-11	3-6-12	4-7-14	6-8-15
	Noise Criteria	—	—	—	13	17	21	24	27	32	36
8" Dia.	Total Pressure	.021	.033	.047	.063	.082	.105	.128	.183	.245	.325
	Airflow, CFM	140	175	210	245	280	315	350	420	490	560
	Throw	1-1-5	1-2-6	1-3-8	2-4-8	3-5-10	3-6-10	4-6-13	5-8-13	6-8-16	7-10-17
	Noise Criteria	—	—	13	17	20	25	28	33	37	40
10" Dia.	Total Pressure	.024	.037	.047	.074	.097	.123	.150	.215	.293	.372
	Airflow, CFM	220	270	330	380	435	490	545	655	765	870
	Throw	1-3-6	2-4-8	3-5-9	4-6-12	5-6-12	5-7-14	6-9-15	6-10-15	8-13-17	9-13-18
	Noise Criteria	—	11	16	20	23	28	31	36	40	43
12" Dia.	Total Pressure	.026	.039	.057	.075	.097	.127	.150	.245	.310	.410
	Airflow, CFM	315	390	470	550	630	705	785	990	1100	1255
	Throw	2-3-7	3-4-9	3-5-10	4-6-13	5-7-13	5-8-15	5-8-16	7-9-18	9-11-18	10-12-19
	Noise Criteria	—	13	18	21	24	29	32	37	41	44
14" Dia.	Total Pressure	.030	.050	.070	.100	.110	.160	.200	.240	.390	.490
	Airflow, CFM	425	530	635	745	850	955	1060	1270	1490	1695
	Throw	3-4-9	4-5-11	4-7-13	5-7-16	6-9-16	7-11-16	7-11-19	9-13-19	11-16-19	11-16-27
	Noise Criteria	—	14	19	22	25	29	32	37	42	45
15" Dia.	Total Pressure	.033	.054	.072	.100	.127	.163	.204	.280	.395	.500
	Airflow, CFM	490	615	735	860	985	1110	1230	1470	1720	1970
	Throw	5-7-10	6-8-11	7-9-14	8-10-17	8-13-18	10-15-19	11-16-22	12-18-27	13-20-32	15-22-34
	Noise Criteria	—	15	20	23	26	30	33	38	43	46

#### Performance Notes:

1. Throws are given at 150, 100 and 50 fpm terminal velocities, under isothermal conditions.
2. All pressures are in inches w.g..
3. The addition of quadrant blanks reduces the effective area and for a given air volume, increases the discharge velocity. This will result in an increase in throw, pressure drop and sound level. To determine throw, select the diffuser as if it were supplying a larger volume of air. The table shows the percentage increase required to determine selection of diffuser size and throw. To correct pressure drop and Noise Criteria, use correction factors as shown for 4-way blow values.

4. Noise Criteria (NC) are based on a room absorption of 10 dB, re 10<sup>-12</sup> watts. Dash (—) in space denotes an Noise Criteria level less than 10.
5. Data derived from independent tests conducted in accordance with ANSI/ASHRAE Standard 70-2006.

Neck Size Diameter in Inches	Nominal Overall Face Size	Ak Factor
6	12 x 12	0.131
8	12 x 12	0.202
6	24 x 24	0.180
8	24 x 24	0.227
10	24 x 24	0.331
12	24 x 24	0.450
14	24 x 24	0.511
15	24 x 24	0.625

Quadrant Blanks (Blow)	% Increase in Air Volume for Throw Determination	% Increase in Static Pressure Drop	NC Sound Level Increase
1 (3-way)	35	125	8
2 (2-way)	100	450	19