

PERFORMANCE DATA:

Model RNS2 • 12 x 12 (300 x 300) Face Size

Nominal Neck Size	Neck Velocity, FPM	400	500	600	700	800	900	1000	1200	1400	1600
	Velocity Pressure	.010	.016	.023	.031	.040	.051	.063	.090	.122	.160
6" Dia.	Total Pressure	.021	.032	.045	.060	.080	.100	.120	.167	.220	.290
	Airflow, CFM	80	100	120	140	160	180	200	235	275	315
	Throw	1-2-6	2-3-8	2-4-10	3-5-11	3-6-12	4-7-13	5-9-14	7-10-15	8-11-17	9-13-18
	Noise Criteria	—	—	—	—	—	—	—	14	24	34
8" Dia.	Total Pressure	.025	.037	.052	.070	.091	.113	.138	.195	.260	.340
	Airflow, CFM	140	175	210	245	280	315	350	420	490	560
	Throw	2-4-10	3-6-13	4-8-15	5-9-16	7-11-17	8-12-19	9-14-20	11-16-22	13-17-23	15-18-26
	Noise Criteria	—	—	—	—	—	—	10	19	27	34

Model RNS2 • 24 x 24 (600 x 600) Face Size

Nominal Neck Size	Neck Velocity, FPM	400	500	600	700	800	900	1000	1200	1400	1600
	Velocity Pressure	.010	.016	.023	.031	.040	.051	.063	.090	.122	.160
6" Dia.	Total Pressure	.026	.040	.058	.080	.104	.131	.190	.262	.350	.500
	Airflow, CFM	80	100	120	140	160	180	200	235	275	315
	Throw	1-2-4	1-2-5	2-2-6	2-3-7	2-4-8	2-4-9	3-5-9	4-6-10	5-7-12	6-8-13
	Noise Criteria	—	—	—	11	14	18	21	27	33	38
8" Dia.	Total Pressure	.043	.065	.092	.125	.165	.210	.257	.400	.540	.740
	Airflow, CFM	140	175	210	245	280	315	350	420	490	560
	Throw	1-3-5	2-3-6	2-4-7	3-4-8	3-5-9	4-5-10	5-6-11	6-7-13	6-8-14	7-9-15
	Noise Criteria	—	11	16	20	23	27	30	37	42	47
10" Dia.	Total Pressure	.045	.069	.098	.137	.176	.225	.274	.421	.568	.774
	Airflow, CFM	220	270	330	380	435	490	545	655	765	870
	Throw	1-3-6	2-3-7	2-4-8	3-4-10	4-5-11	5-6-12	5-7-13	6-8-14	7-9-15	8-10-16
	Noise Criteria	10	15	20	24	28	32	35	40	45	50
12" Dia.	Total Pressure	.046	.070	.100	.140	.180	.230	.280	.430	.580	.790
	Airflow, CFM	315	390	470	550	630	705	785	990	1100	1255
	Throw	3-4-7	4-5-9	4-6-10	5-7-11	6-8-12	7-9-13	7-10-14	8-11-15	9-12-16	10-13-17
	Noise Criteria	11	16	21	25	29	33	36	41	46	51
14" Dia.	Total Pressure	.047	.072	.104	.145	.185	.240	.285	.440	.590	.805
	Airflow, CFM	425	530	635	745	850	955	1060	1270	1490	1695
	Throw	3-4-7	4-5-9	4-6-10	5-7-11	6-8-12	7-9-13	7-10-14	8-11-15	9-12-16	10-13-17
	Noise Criteria	13	18	23	27	31	34	37	43	53	57
15" Dia.	Total Pressure	.048	.075	.110	.150	.195	.250	.300	.455	.610	.825
	Airflow, CFM	490	615	735	860	985	1110	1230	1470	1720	1970
	Throw	4-5-8	4-6-10	5-7-11	6-8-12	6-9-13	7-10-14	8-10-15	9-12-16	10-13-17	11-14-18
	Noise Criteria	14	19	24	29	32	36	39	45	56	60

Performance Notes:

1. Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions.

2. All pressures are in inches w.g.. To obtain static pressure, subtract the velocity pressure from the total pressure.

3. Noise Criteria (NC) values are based upon 10dB room absorption, re 10⁻¹² watts. Dash (—) in space indicates an Noise Criteria of less than 15.

4. Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70 – 2006.

Neck Size Diameter in Inches	Nominal Overall Face Size	Ak Factor
6	12 x 12	.157
	12 x 12	.232
6	24 x 24	.185
	24 x 24	.226
10	24 x 24	.285
12	24 x 24	.382
14	24 x 24	.505
15	24 x 24	.577